

## Spring Retractable Pre-Rinse/Potable Water Reels

Water - 3/8", 1/2" I.D.



### Potable Water

- Stainless steel, full flow shaft and CPVC swivel
- Suitable for use as a drinking water system component (does not include NSF/ANSI 61 Certification)
- Maximum operating temperature 73 °F (23 °C)

### Pre-Rinse

- Lever-operated spray valve is included
- Optional 360° rotating swivel (600248) offers 20° of angular motion
- Push-Lok®, field replaceable, hose end fittings
- Rated for hot water up to 180 °F (82 °C)



A5835 OLBSW23



Spray Valve  
S600080

| Model with hose & bumper   | Shipping Weight |    | Hose I.D. |    | Hose O.D. |    | Hose Length |    | Max Pressure |     | NPT(M) Reel Inlet | NPT(F) Reel Outlet | Size Index Page | Size Index # |
|--|-----------------|----|-----------|----|-----------|----|-------------|----|--------------|-----|-------------------|--------------------|-----------------|--------------|
|  | lbs             | kg | in        | mm | in        | mm | ft          | m  | psi          | bar | in                | in                 |                 |              |
| <b>Potable (Drinking) Water Hose Reel</b> Garden-style hose end. Maximum temperature 73 °F (23 °C) |                 |    |           |    |           |    |             |    |              |     |                   |                    |                 |              |
| A5835 OLBSW23  | 28              | 13 | 1/2       | 13 | .781      | 20 | 35          | 11 | 150          | 10  | 1/2               | 3/8                | 10              | 1            |

| Model with hose & bumper   | Shipping Weight |    | Hose I.D. |    | Hose O.D. |    | Hose Length |    | Max Pressure |     | NPT(M) Hose Outlet | NPT(F) Reel Inlet | NPT(F) Reel Outlet | Size Index Page | Size Index # |
|--|-----------------|----|-----------|----|-----------|----|-------------|----|--------------|-----|--------------------|-------------------|--------------------|-----------------|--------------|
|  | lbs             | kg | in        | mm | in        | mm | ft          | m  | psi          | bar | in                 | in                | in                 |                 |              |
| <b>Pre-Rinse Hose Reels</b> Maximum temperature 180 °F (82 °C) *Enclosed model |                 |    |           |    |           |    |             |    |              |     |                    |                   |                    |                 |              |
| 4625 OLPSW5  | 22              | 10 | 3/8       | 10 | .660      | 17 | 25          | 8  | 125          | 9   | 3/8                | 3/8               | 1/4                | 9               | ---          |
| 5635 OLPSW5  | 27              | 12 | 3/8       | 10 | .660      | 17 | 35          | 11 | 125          | 9   | 3/8                | 3/8               | 1/4                | 10              | 1            |
| 5635 ELPSW5*   | 37              | 17 | 3/8       | 10 | .660      | 17 | 35          | 11 | 125          | 9   | 3/8                | 3/8               | 1/4                | 11              | 1            |
| 5635 OLSSW5**  | 28              | 13 | 3/8       | 10 | .660      | 16 | 35          | 11 | 125          | 9   | 3/8                | 3/8               | 1/4                | 10              | 1            |



**Interactive Reel Catalog**

Visit [reelcraft.com/catalog](http://reelcraft.com/catalog) for complete product specifications, parts, and accessories.



**Pivot Bases & Swing Brackets**  
See page 43

## Stainless Steel Fluid Path Reels

Chemical Delivery - 3/8", 1/2", 3/4", 1" I.D.

- Offers another level of protection in corrosive environments
- Stainless steel swivel and stainless steel main shaft - all components in contact with media
- Cast aluminum ratchet and latch pawl provide reliability and durability
- By design, the ratchet and latch pawl are substantially thicker than competing reels to reduce wear and increase service life
- Steel components are individually powder coated prior to assembly to maximize corrosion resistance
- Standard seals are FKM



HD79005 OLB



| Model without hose & bumper  | Shipping Weight |    | Hose Capacity |      |        | Max Pressure | NPT(F) Reel Inlet | NPT(F) Reel Outlet | Size Index Page | Size Index # |     |     |    |   |
|--|-----------------|----|---------------|------|--------|--------------|-------------------|--------------------|-----------------|--------------|-----|-----|----|---|
|  | lbs             | kg | I.D.          | O.D. | Length |              |                   |                    |                 |              |     |     |    |   |
| <b>Low Pressure Air/Water Reels</b> Maximum Temperature 210 °F (99 °C) |                 |    |               |      |        |              |                   |                    |                 |              |     |     |    |   |
| HD78005 OLB  | 54              | 24 | 1/2           | 13   | .750   | 19           | 75                | 23                 | 500             | 35           | 1/2 | 1/2 | 13 | 2 |
| HD79005 OLB  | 54              | 24 | 3/4           | 19   | 1.075  | 27           | 50                | 15                 | 500             | 35           | 3/4 | 3/4 | 13 | 2 |
| E9305 OLBBW  | 115             | 52 | 3/4           | 19   | 1.075  | 27           | 100               | 30                 | 500             | 35           | 3/4 | 3/4 | 16 | 2 |
| D9400 OLBBW  | 115             | 52 | 1             | 25   | 1.375  | 35           | 50                | 15                 | 500             | 35           | 1   | 1   | 16 | 1 |
| <b>Medium Pressure Oil Reels</b> Maximum Temperature 210 °F (99 °C)    |                 |    |               |      |        |              |                   |                    |                 |              |     |     |    |   |
| HD76000 OMB  | 45              | 20 | 3/8           | 10   | .690   | 18           | 50                | 15                 | 3000            | 207          | 1/2 | 1/2 | 13 | 1 |



**Pivot Bases & Swing Brackets**  
See page 43

**NEW!**  
**Reel Covers**

See page 41

