

Spring Retractable Pre-Rinse/Potable Water Reels

Water - 3/8", 1/2" I.D.



Potable Water

- Stainless steel, full flow shaft and CPVC swivel
- Suitable for use as a drinking water system component (does not include NSF/ANSI 61 Certification)
- Maximum operating temperature 73 °F (23 °C)

Pre-Rinse

- Lever-operated spray valve is included
- Optional 360° rotating swivel (600248) offers 20° of angular motion
- Push-Lok®, field replaceable, hose end fittings
- Rated for hot water up to 180 °F (82 °C)



A5835 OLBSW23



Spray Valve
S600080

Model with hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in		
Potable (Drinking) Water Hose Reel Garden-style hose end. Maximum temperature 73 °F (23 °C)														
A5835 OLBSW23	28	13	1/2	13	.781	20	35	11	150	10	1/2	3/8	10	1

Model with hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in		
Pre-Rinse Hose Reels Maximum temperature 180 °F (82 °C) *Enclosed model															
4625 OLPSW5	22	10	3/8	10	.660	17	25	8	125	9	3/8	3/8	1/4	9	---
5635 OLPSW5	27	12	3/8	10	.660	17	35	11	125	9	3/8	3/8	1/4	10	1
5635 ELPSW5*	37	17	3/8	10	.660	17	35	11	125	9	3/8	3/8	1/4	11	1
5635 OLSSW5**	28	13	3/8	10	.660	16	35	11	125	9	3/8	3/8	1/4	10	1



Interactive Reel Catalog

Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.



Pivot Bases & Swing Brackets
See page 43

Stainless Steel Fluid Path Reels

Chemical Delivery - 3/8", 1/2", 3/4", 1" I.D.

- Offers another level of protection in corrosive environments
- Stainless steel swivel and stainless steel main shaft - all components in contact with media
- Cast aluminum ratchet and latch pawl provide reliability and durability
- By design, the ratchet and latch pawl are substantially thicker than competing reels to reduce wear and increase service life
- Steel components are individually powder coated prior to assembly to maximize corrosion resistance
- Standard seals are FKM



HD79005 OLB



Model without hose & bumper	Shipping Weight		Hose Capacity			Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #				
	lbs	kg	I.D.	O.D.	Length									
Low Pressure Air/Water Reels Maximum Temperature 210 °F (99 °C)														
HD78005 OLB	54	24	1/2	13	.750	19	75	23	500	35	1/2	1/2	13	2
HD79005 OLB	54	24	3/4	19	1.075	27	50	15	500	35	3/4	3/4	13	2
E9305 OLBBW	115	52	3/4	19	1.075	27	100	30	500	35	3/4	3/4	16	2
D9400 OLBBW	115	52	1	25	1.375	35	50	15	500	35	1	1	16	1
Medium Pressure Oil Reels Maximum Temperature 210 °F (99 °C)														
HD76000 OMB	45	20	3/8	10	.690	18	50	15	3000	207	1/2	1/2	13	1



Pivot Bases & Swing Brackets
See page 43

NEW!
Reel Covers



See page 41

Stainless Steel Hose Reels

Air/Water/Oil - 3/8", 1/2", 3/4", 1" I.D.

- Electropolished 304L stainless steel
- Ideal for applications where the harsh environment requires the use of stainless steel hose reels
- Stainless steel components offer the maximum protection from premature corrosion
- Swivel includes FKM O-rings



7800 OLS

See page 33 for Stainless Steel Cord Reels



D9300 OLSBW

Spring Retractable Reels Note: Standard latch parts are made from aluminum. Series 80000 and D80000 stainless reels have an aluminum fluid path. Stainless latch parts and fluid path are available in the -S part numbers (example: OLS-S).

Manual Crank Reels Note: The -S models include all stainless steel hubs and bushings and are ideal for high humidity and corrosive environments. Refer to reelcraft.com for stainless steel models with aluminum hubs and bronze bushings.

Model without hose & bumper	Shipping Weight		Hose Capacity				Max Pressure		NPT(F) Reel Inlet		NPT(F) Reel Outlet		Size Index Page	Size Index #
	lbs	kg	I.D.		O.D.		psi	bar	in	in	in	in		
Spring Retractable Low Pressure Air/Water Reels Maximum Temperature 210 °F (99 °C)														
5600 OLS	22	10	3/8	10	.600	15	35	11	500	35	3/8	3/8	10	1
5600 OLS-S	22	10	3/8	10	.600	15	35	11	500	35	3/8	3/8	10	1
7800 OLS	41	19	1/2	13	.750	19	50	15	500	35	1/2	1/2	12	---
7800 OLS-S	41	19	1/2	13	.750	19	50	15	500	35	1/2	1/2	12	---
82000 OLS	81	37	1/2	13	.750	19	100	30	500	35	1/2	1/2	14	1
82000 OLS-S	81	37	1/2	13	.750	19	100	30	500	35	1/2	1/2	14	1
83000 OLS	81	37	3/4	19	1.188	30	50	15	500	35	3/4	3/4	14	1
83000 OLS-S	81	37	3/4	19	1.188	30	50	15	500	35	3/4	3/4	14	1
D83000 OLS	84	38	3/4	19	1.188	30	75	23	500	35	3/4	3/4	14	2
D83000 OLS-S	84	38	3/4	19	1.188	30	75	23	500	35	3/4	3/4	14	2
D9300 OLSBW	116	53	3/4	19	1.188	30	75	23	500	35	3/4	3/4	16	1
D9300 OLSBW-S	116	53	3/4	19	1.188	30	75	23	500	35	3/4	3/4	16	1
D84000 OLS	92	42	1	25	1.375	35	50	15	500	35	1	1	14	3
D84000 OLS-S	92	42	1	25	1.375	35	50	15	500	35	1	1	14	3
D9400 OLSBW	117	53	1	25	1.375	35	50	15	500	35	1	1	16	1
Spring Retractable Medium Pressure Oil Reels Maximum Temperature 210 °F (99 °C)														
5600 OMS	24	11	3/8	10	.710	18	30	9	3000	207	3/8	3/8	10	1
5600 OMS-S	24	11	3/8	10	.710	18	30	9	3000	207	3/8	3/8	10	1
7600 OMS55	42	19	3/8	10	.710	18	66	20	3000	207	3/8	3/8	12	---
7600 OMS55-S55	42	19	3/8	10	.710	18	66	20	3000	207	3/8	3/8	12	---
7800 OMS	43	20	1/2	13	.850	22	50	15	3000	207	1/2	1/2	12	---
7800 OMS-S	43	20	1/2	13	.850	22	50	15	3000	207	1/2	1/2	12	---
82000 OMS-S	83	38	1/2	13	.850	22	75	23	1500	103	1/2	1/2	14	1
83000 OMS	83	38	3/4	19	1.188	30	50	15	1250	86	3/4	3/4	14	1

Interactive Reel Catalog
Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.

Hose Assemblies & Bumper Stops
See page 40



HS18000 M-S

Model without hose & bumper	Shipping Weight		Pressure		NPT(F) Outlet		NPT(F) Inlet		I.D.		O.D.		Size Index Page	Size Index #			
	lbs	kg	psi	bar	in	in	in	in	in	in	in	in					
Hand Crank Low/Medium Pressure Reels Maximum temperature 210 °F (99 °C)																	
HS18000 M-S	36	16	3000	207	1/2	1/2	Hose Capacity	425	130	300	91	200	61	25	1		
HS19000 M-S	38	17	3000	207	3/4	3/4		425	130	300	91	200	61	75	23	25	1
HS37000 L	47	21	500	35	1 (M)	1		---	---	---	---	---	---	---	---	100	30