



## Type A Adapters adapter x female NPT

**Feature:**

- Pressure rating is based on the seal of the mating part. See ratings on page 124.

Size	356T6 Aluminum Part #	Aluminum Hard Coat Part #	Brass Part #
1/2"	<b>50-A-AL</b> <sup>2</sup>	---	<b>50-A-BR</b>
3/4" x 1/2"	<b>7550-A-AL</b> <sup>2</sup>	---	<b>7550-A-BR</b>
3/4"	<b>75-A-AL</b> <sup>2</sup>	---	<b>75-A-BR</b>
1"	<b>100-A-AL</b> <sup>2</sup>	---	<b>100-A-BR</b>
1 1/4"	<b>125-A-AL</b>	---	<b>125-A-BR</b>
1 1/2"	<b>150-A-AL</b>	<b>150-A-ALH</b>	<b>150-A-BR</b>
2"	<b>200-A-AL</b>	<b>200-A-ALH</b>	<b>200-A-BR</b>
2 1/2"	<b>250-A-AL</b>	---	<b>250-A-BR</b>
3"	<b>300-A-AL</b>	<b>300-A-ALH</b>	<b>300-A-BR</b>
4"	<b>400-A-AL</b>	<b>400-A-ALH</b>	<b>400-A-BR</b>
5"	<b>500-A-AL</b>	---	<b>500-A-BR</b>
6"	<b>600-A-AL</b>	<b>600-A-ALH</b>	<b>600-A-BR</b>
8" DIX	<b>800-A-AL</b> <sup>1</sup>	---	---
8" BL	<b>801-A-AL</b> <sup>1</sup>	---	---



356T6 aluminum



aluminum hardcoat



brass



unplated malleable iron



plated malleable iron



316 stainless steel

<sup>1</sup> Dixon® and Boss-Lock™ cam & groove couplings *do not interchange in the 8" size.*

<sup>2</sup> made from 6061-T6 aluminum



Size	Unplated Malleable Iron Part #	Plated Malleable Iron Part #	316 Stainless Steel Part #
1/2"	---	---	<b>50-A-SS</b>
3/4" x 1/2"	---	---	<b>7550-A-SS</b>
3/4"	---	<b>75-A-PM</b>	<b>75-A-SS</b>
1"	---	<b>100-A-PM</b>	<b>100-A-SS</b>
1 1/4"	---	---	<b>125-A-SS</b>
1 1/2"	<b>150-A-MI</b>	<b>150-A-PM</b>	<b>150-A-SS</b>
2"	<b>200-A-MI</b>	<b>200-A-PM</b>	<b>200-A-SS</b>
2 1/2"	---	---	<b>250-A-SS</b>
3"	<b>300-A-MI</b>	<b>300-A-PM</b>	<b>300-A-SS</b>
4"	<b>400-A-MI</b>	<b>400-A-PM</b>	<b>400-A-SS</b>
5"	<b>500-A-MI</b>	---	<b>500-A-SS</b>
6"	---	<b>600-A-PM</b> <sup>1</sup>	<b>600-A-SS</b>

<sup>1</sup> ductile iron

### adapter x female NPT with abrasion resistant inserts

**Feature:**

- used in extreme abrasion transfer applications such as sand transfer in hydraulic fracturing

Description	UHMW Polyethylene Insert Part #
<b>(400-A-AL)</b> aluminum adapter x female NPT with UHMW insert	<b>400-A-ALINSERT</b>
<b>(400-A-BR)</b> brass adapter x female NPT with UHMW insert	<b>400-A-BRINSERT</b>
<b>(400-A-MI)</b> malleable iron adapter x female NPT with UHMW insert	<b>400-A-MIINSERT</b>
<b>(400-A-SS)</b> stainless steel adapter x female NPT with UHMW insert	<b>400-A-SSINSERT</b>

Replacement inserts are available on page 172.



400-A-ALINSERT

Cam & Groove

